

GS-X12C-RW3S

Model: GS-X12C-RW3S		Features
		♦ Simple installation, convenient use, wireless network connection.
		♦ The image is clear and smooth, and the intelligent transmission exerts the limit of the network
		♦ Online firmware upgrade, synchronous update function and physical examination
		♦ Support two-way voice intercom, echo cancellation, noise suppression
		♦ Support Android, IOS smart terminal remote real-time monitoring
		♦ 300W high-definition pixels (2304X1296), clear picture quality
		♦ Supports 2.4G Wi Fi (IEEE802.11b/g/n)
		♦ Intelligent push, filter out useless information
		♦ Intelligent storage algorithm, small space can accommodate more content, support Micro SD card, cloud storage
		♦ Support hotspot distribution network connection
		♦ Support humanoid detection, motion detection
		♦ Small and exquisite appearance
		♦ Support device sharing function (support sharing multiple friends)
		♦ Dual-light infrared lights, 24-hour monitoring day and night, IR-CUT switching, no color cast during the day, clearer night vision
Specifications		
System	SOC	Embedded LINUX operating system
Image Sensor	Sensor	1/2.9 CMOS sensor
	Lens	4mm, F2.0, 4MP
	Viewing angle	Diagonal 91.8° Horizontal 78° Vertical 38°
	Minimum illumination	Day mode 1Lux, night vision mode 0.01Lux
Audio	Audio input	Sensitivity - 42dB
	Audio output	External 8Ω / 1W speaker
	Two-way intercom	full duplex
Video	Video compression method	H.265
	Video stream	135kbps-2048kbps
	Image frame rate	15 fps
	Maximum image size	2304*1296 (3MP)
	Night vision light source	IRCUT filter automatic switching
	Day and night mode	Smart Dual Light
Network	Wireless network	Built-in 2.4GWIFI antenna
	Wireless standard	2.4GHz Wi-Fi (IEEE 802.11b/g/n)
	Supporting agreement	TCP/IP, UDP/IP, DHCP, MUTP
	Support IP address	Dynamic IP address
Video	Video mode	Mobile recording, alarm recording, timed recording, and humanoid recording
	Video storage	Cloud storage, local Micro SD card (up to 256G)
Function	Intelligent	Humanoid detection, motion detection
	Alarm notification	Mobile APP message push
PTZ	PTZ rotation angle	H (horizontal) 0° ~ 350° stepless rotation; V (vertical) 60° ~ -20°
Power supply	Operating Voltage	5V, 1.5A
Environment	Working environment	-10° ~ 45°C /10% ~ 80% (no condensation)
	Storage environment	-20°C ~ 60° /0% ~ 90% (no condensation)