

GS-X95-RX2B

Model: GS-X95-RX2B		Features
		• Simple installation, convenient use, wireless network connection.
		• The image is clear and smooth, and intelligent transmission maximizes the limits of the network
		• Online firmware upgrade, synchronous update function and physical examination
		• Supports two-way voice intercom, echo cancellation, and noise suppression
		• Support Android, IOS smart terminal remote real-time monitoring
		• 2MP high-definition pixels (1920X1080), clear picture quality
		• Dual lenses and dual pictures can be viewed on the same screen, monitoring different viewing angles respectively, and saying goodbye to surveillance blind spots.
		• Intelligent push, filter out useless information
		• Intelligent storage algorithm, small space can accommodate more content, supports Micro SD card (maximum support 128G), cloud storage
		• Support hotspot distribution network connection
		• Support humanoid detection and motion detection
		• Supports preset position setting and calling functions, supporting up to 6 preset points
		• Supports device sharing function (supports sharing with multiple friends) and device management identity transfer function
		• Dual-light infrared lights, 24-hour day and night monitoring, IR-CUT switching, no color cast during the day, and clearer night vision
Specifications		
System	SOC	Embedded LINUX operating system
Image Sensor	Sensor	Dual 1/3.2 CMOS sensor
	Lens	Dome camera lens: f: 6.0mm, F2.1, 3MP
		Bolt lens: f: 2.8mm, F2.0, 3MP
	Viewing angle	Dome camera lens: diagonal 47°, horizontal 40°, vertical 21.3°
		Fixed camera lens: diagonal angle 110°, horizontal 77°, vertical 53°
	Minimum illumination	Day mode 1Lux, night vision mode 0.01Lux
Audio	Audio input	Sensitivity - 42dB
	Audio output	External 8Ω/MAX 2W speaker
	Two-way intercom	Full duplex
Video	Video compression method	H.264
	Video stream	135kbps-2048kbps
	Image frame rate	Self-adaptive
	Maximum image size	1920*1080P
	Night vision light source	IRCUT filter automatically switches, 4 white light lamps, 8 infrared lamps (850nm wavelength), irradiation distance: 7 meters
	Day and night mode	Smart dual light/smart full color/smart infrared
Network	Wireless network	Built-in 2.4GWIFI antenna
	Wireless standards	2.4GHz Wi-Fi (IEEE 802.11b/g/n)
	Supporting agreement	HTTP,TCP/IP,IPv4,UPNP,RTSP, UDP, SMTP, NTP, DHCP, DNS
	SupportIPaddress	DynamicIPaddress
Recording	Video recording method	All-day recording, alarm recording, scheduled recording
	Video storage	Cloud storage, local Micro SD card (up to 128G supported)
Function	Intelligent	Humanoid detection, motion detection
	Audible alarm	When equipped with a dual-light light panel, it supports audible and visual alarms.
	Alarm notification	Mobile APP message push
PTZ	PTZ rotation angle	H (horizontal) 0° ~ 350° infinite rotation; V (vertical) 60° ~ -20°
	Preset position	Supports 6 preset position settings
Power Supply	Operating Voltage	5V, 1.5A
Environment	Working environment	-10°C ~ 45°C
	Storage environment	-20°C ~ 60°C