

GS-X56-RH4W

(4MP) Battery PT Camera



- Dual channel 2MP HD image
- Full-duplex 2-way voice real-time talk
- 128GB TF card storage
- Dual channel screen
- Instant Notifications
- Support for humanoid tracking
- True Wireless
- IP65 Waterproof and Dustproof

H264 encoding, lower bit rate, clearer image quality, less bandwidth occupied, longer storage time of TF card.

Support humanoid tracking, position monitoring, and automatic calibration functions;

Built in 8000mAh low-power battery,

Support solar power supply - connect solar panels to bid farewell to power outages.

Support low power consumption mode and Constant power mode

APP support 17 languages;

SimplifiedChinese/TraditionalChinese/English/Fin nish/Korean/French/Portuguese/Thai/Spanish/Polish/Indonesian/German/Italian/Russian/Japanese/Vietnamese/Arabic/Turkish



















Specifications

<u>Specifications</u>	
	GS-X56-RH4W
Camera	00 AU III-W
Model	
Main processor	Ingenic T23ZN
Operating system	Embedded LINUX operating system
Video	
Imaging devices	1/3" CMOS Sensor
Video encoding standards	H.264
System format	PAL 50HZ/NTSC 60HZ
Effective resolution	2560*1440
Video frame rate	12fps
Minimum illuminance	Day mode 1Lux,night mode0.01Lux
Day and night mode	Auto
Video output	Mobile APP client
Capture function	Support
Audio	
Encoding standard	G.711U
Audio input	external MIC. An analog MIC with a signal-to-noise ratio of 42DB
Audio output	External 8Ω/MAX IW speakers
Voice calls	Support full-duplex voice call function
Recording management	
Recording mode	Alarm trigger, manual recording
Video saving	local Micro SD card, phone memory
Alarm	
Smart function	Support humanoid tracking, position monitoring, and automatic calibration functions;
Alarm notification	Mobile APP message push, alarm sound warning.
	DUIDA INT INT INT INT INT INT
LIE-FUU	
	Flow Recharge&query
	10
	Cupparts up to 1900D
	-10 43
	201
	ZOIIIII ZUY,JIIIII (WILI BOX.) Approximately 16.16
Flow Recharge&query Call One-click call Other TF card capacity Capabilicty Operating voltage Work environment General Dimensions Weight Carton Meas Carton Weight	B1/B3/B5/B7/B8/B20/B28 Flow Recharge&query no Supports up to 1286B 8000mAh 5V -10°C 45°C 28lmm*209.5mm*189.5mm (with box) Approximately 1.64 kg 584mm*580mm*4444mm (12pcs/ctn) Approximately 20.6 kg